

H31 COPING SYSTEM



TO BE INCORPORATED IN TO CLADDING SPECIFICATIONS AND READ WITH PRELIMINARIES/GENERAL CONDITIONS

TYPE OF CLADDING

Plasmet secret fix coping system comprising of 2mm/3mm thick aluminium polyester powder coated coping secured by the SF600 aluminium support clip.

Coping and support clip has been formally tested at an independent test centre up to a simulated wind suction load of 36.8 kN/m.

522 CAPPING SYSTEM

- **Drawing reference(s):** N/A
- **Primary support structure:)** *By others*
- **Manufacturer and Reference:** Plasmet Limited, Barton Moss Road, Eccles, Manchester M30 7RL
Telephone: 0161 707 3141
Fax: 0161 788 0181
Email: sales@plasmet.co.uk Web: www.plasmet.co.uk
- **Type:** Plasmet Secret Fix Coping System
- **Material:** For polyester powder coated aluminium; Aluminium to EN485 in 4015 H12 series alloy
- **Thickness:** 2mm/3mm (*delete as applicable*)
- **Finish:** Polyester Powder Coated to BS3987 by approved powder coating applicator
- **Colour:** (*insert colour reference from manufacturers colour chart*)
- **Fixings:** No exposed fixings. Coping secured by hooking over secret fix support straps.
- **Joint type:** Plasmet SF600 proprietary extruded aluminium fixing clip, typically at 1000mm centres, with anti-rattle EPDM extrusions. No sealants or mastics to be used. Aluminium levelling fixing brackets.
- **Joint width:** 3mm expansion gap

H31 COPING SYSTEM



- **Installation:** Number and location of fasteners as per structural design.
- **Other requirements:** Note - Care must be taken with regards to bi-metallic corrosion between metals.