

# H72 ALUMINIUM STRIP/SHEET/COVER FLASHINGS



**TO BE INCORPORATED IN TO CLADDING SPECIFICATIONS AND READ WITH  
PRELIMINARIES/GENERAL CONDITIONS**

## 480 SOFFIT

- **Drawing reference(s):** N/A
- **Manufacturer and Reference:** Plasmet Limited, Barton Moss Road, Eccles, Manchester M30 7RL  
Telephone: 0161 707 3141  
Fax: 0161 788 0181  
Email: [sales@plasmet.co.uk](mailto:sales@plasmet.co.uk) Web: [www.plasmet.co.uk](http://www.plasmet.co.uk)
- **Product Reference:** Plasmet Standard Recessed Soffit System
- **Material:** For polyester powder coated aluminium; Aluminium to EN485 in 4015 H12 series alloy. Galvanised Steel to EN10143/Z2:1993
- **Shape:** Recessed joint. Stiffened with support ribs as necessary to meet performance criteria under wind load. Profile as Plasmet drawing
- **Size:**  
Soffit width \_\_\_\_\_ mm (*insert cover width*) length \_\_\_\_\_ mm (*insert cover length*)
- **Thickness:** 2mm/3mm (*delete as applicable*)
- **Finish:** Polyester Powder Coated to BS3987 by approved powder coating applicator
- **Colour:** (*insert colour reference from manufacturers colour chart*)
- **Fixings:** Stainless Steel low dome self drilling fixings/Stainless Steel Rivetts (*delete as applicable*). Number and location of fasteners: As per structural design
- **Method of Jointing:** Assembled directly onto framework work with overlapping recessed joints. EPDM fir-tree gasket inserted along recessed joints (*delete if not required*)
- **Joint width:** 20/25mm (*delete as applicable*) recessed joint
- **Other requirements:** Preformed ventilation slots equal to a continuous strip ... mm wide, slots sized to stop the ingress of nesting, winged insects. (*Delete if not required*).